

Cutting TF2

TF2

TF2 is ideal for cutting flexible hydraulic hoses up to 2" four spirals and 1"1/2 six spirals.

MAIN FEATURES:

- Ø 250 mm serrated blade;
- mechanical pedal control;
- recessed blade and guards for the operator's safety.

Product specifications could be modified without prior notice.



| | |
|---------------------------------|---|
| 6 SPIRALS | 1" 1/2 |
| 4 SPIRALS | 2" |
| 2 BRAIDS | 2" |
| MAX. Diam. | 75 mm (2.953") |
| REVOLUTIONS/MINUTE | 2900 |
| BLADE Diam. | 250 mm (9.843") |
| STANDARD VOLTAGE | 400V 50HZ3PH |
| DIMENSIONS L x W x H | 840x550x1150 mm (33.070"x21.654"x45.276") |
| WEIGHT | 130 KG (290 Lbs) |
| MOTOR POWER | 3 Kw (4 Hp) |
| SAFETY PROTECTION | incl. |
| SUCTION CONNECTION | incl. |
| MEASURING HOSE HOLDER | OPTIONAL |
| CENTRING DEVICE + METER COUNTER | OPTIONAL |
| STROKE COUNTER | OPTIONAL |
| SPECIAL VOLTAGE | OPTIONAL |